


Cylindrical Head Ejector Pins

DIN 1530 / ISO 6751

kalipyansan®

401.



MATERIAL

BODY HARDNESS

HEAD HARDNESS

MATERIAL CODE

1.2210 Tool Steel

60 ± 2 HRC

35 ± 3 HRC

WS

1.2344 Hot Work Steel

45 ± 3 HRC

35 ± 3 HRC

NWS

401.

d g6	d1-0,2	R	k-0,05	l+2					
				100	125	160	200	250	315
2,0	4,0			●	●	●	●		
2,2				●	●	●	●		
2,5	5,0			●	●	●	●	●	
2,7				●	●	●	●		
3,0				●	●	●	●	●	
3,2	6,0			●	●	●	●	●	
3,3				●	●	●	●	●	
3,5	7,0			●	●	●	●	●	
4,0				●	●	●	●	●	
4,2	8,0			●	●	●	●	●	●
4,5				●	●	●	●	●	●
5,0				●	●	●	●	●	●
5,5	10,0			●	●	●	●	●	●
6,0				●	●	●	●	●	●
7,0	12,0			●	●	●	●	●	●
8,0	14,0			●	●	●	●	●	●
10,0	16,0			●	●	●	●	●	●
12,0	20,0	0,8	7,0	●	●	●	●	●	●

ORDER EXAMPLE

Ejector Pin Code : 401.
Diameter (d=4,0) : 0400.
Length (l=160) : 160.
Material Code : WS
Order Code : 401.0400.160.WS

ORDER EXAMPLE

Ejector Pin Code : 401.
Diameter (d=8,0) : 0800.
Length (l=125) : 125.
Material Code : NWS
Order Code : 401.0800.125.NWS